



**Marshland.  
The solution for waterlogged  
and marshy terrain.**



# Marshland

Specialized line for use on waterlogged and marshy terrain.

The extremely deep lugs, together with the structure of the carcass, provide high traction and floatation.

SIZE	Tread Pattern	SW mm	OD mm	SLR mm	RC mm	SRI	Rim	Permitted Rims	Type	Tube
<b>340/85R38</b> 139A8 (139B)	<b>MARSHLAND</b>	405	1660	760	4970	775	W13	W11-W12-DW11DW12-DW13	TUBELESS	16.9-38 TR218
<b>PRESSURE</b>										
psi	<b>12</b>	<b>14</b>	<b>17</b>	<b>20</b>	<b>23</b>	<b>26</b>	<b>29</b>			
bar	<b>0,8</b>	<b>1,0</b>	<b>1,2</b>	<b>1,4</b>	<b>1,6</b>	<b>1,8</b>	<b>2,0</b>			
<b>MAX. LOAD kg</b>										
50 S	1560	1775	1995	2215	2430					
<b>40 S</b>	1560	1775	1995	2215	<b>2430</b>					
30 S	1665	1900	2135	2370	2605					
10 LT S	2120	2415	2710	3010	3305	3475	3645			
10 HT S	1665	1900	2135	2370	2605					

SIZE	Tread Pattern	SW mm	OD mm	SLR mm	RC mm	SRI	Rim	Permitted Rims	Type	Tube
<b>420/85R38</b> 144A8 (144B)	<b>MARSHLAND</b>	460	1745	795	5220	800	W15L	W14L-DW14L-DW15L	TUBELESS	16.9-38 TR218
<b>PRESSURE</b>										
psi	<b>12</b>	<b>14</b>	<b>17</b>	<b>20</b>	<b>23</b>	<b>26</b>	<b>29</b>			
bar	<b>0,8</b>	<b>1,0</b>	<b>1,2</b>	<b>1,4</b>	<b>1,6</b>	<b>1,8</b>	<b>2,0</b>			
<b>MAX. LOAD kg</b>										
50 S	1795	2045	2300	2550	2800					
<b>40 S</b>	1795	2045	2300	2550	<b>2800</b>					
30 S	1920	2190	2460	2730	3000					
10 LT S	2440	2780	3125	3470	3810	4005	4200			
10 HT S	1920	2190	2460	2730	3000					

SIZE	Tread Pattern	SW mm	OD mm	SLR mm	RC mm	SRI	Rim	Permitted Rims	Type	Tube
<b>460/85R38</b> 149A8 (149B)	<b>MARSHLAND</b>	499	1810	815	5420	825	W16L	W15L-DW15L-DW16L	TUBELESS	18.4-38 TR218
<b>PRESSURE</b>										
psi	<b>12</b>	<b>14</b>	<b>17</b>	<b>20</b>	<b>23</b>	<b>26</b>	<b>29</b>			
bar	<b>0,8</b>	<b>1,0</b>	<b>1,2</b>	<b>1,4</b>	<b>1,6</b>	<b>1,8</b>	<b>2,0</b>			
<b>MAX. LOAD kg</b>										
50 S	2080	2375	2665	2960	3250					
<b>40 S</b>	2080	2375	2665	2960	<b>3250</b>					
30 S	2230	2540	2855	3165	3480					
10 LT S	2830	3230	3625	4025	4420	4650	4875			
10 HT S	2230	2540	2855	3165	3480					



Follow us



Yokohama TWS S.p.A.  
Via Nazionale Tiburtina, 143 - 00019 Villa Adriana - Tivoli (RM), Italy  
Phone: +39 0774 3841 – info.tws@yokohama-tws.com  
www.trelleborg-tires.com

