

T-900

Best handling
for demanding applications



TIRE LIFE



**PUNCTURE
RESISTANCE**



**COOL
RUNNING**



STABILITY

Designed for demanding applications, the T-900 delivers optimal performance for crucial tasks. Its block tread design and large footprint minimize specific pressure, reduce downtime, and maximize tire life.

The shock-absorbing structure, reinforced sidewalls, and rim guards, protect against impact damage, while the anti-slip bead wire system ensures stability. The T-900 tire provides greater stability for faster load positioning and improved cornering, enhancing efficiency and maintaining a low internal temperature for maximum uptime.

T-900

BIAS PNEUMATIC - MAXIMUM INTENSITY APPLICATIONS

TREAD PATTERNS



T-900

Size	Alternative Size	Ply Rating	Rim	Product Dimensions [mm]			Minimal Dual Spacing [mm]	Inflation Pressure [bar]	Tire Type	Load Index	Speed Symbol	Load Capacity [kg]	
				Overall Diameter	Section Width	Tread Depth						Counterbalanced Lift Trucks up to 25 km/h	
												Load Wheel	Steering Wheel
5.00-8		10	3.00D-8	468	140	13	158	10,00	TT	111	A5	1.415	1.090
18x7-8	180/70-8	16	4.33R-8	462	168	16	199	10,00	TT	125	A5	2.145	1.650
6.00-9		12	4.00E-9	543	160	15	192	10,00	TT	121	A5	1.885	1.450
23x9-10	225/75-10	20	6.50F-10	585	230	19	259	10,00	TT	142	A5	3.445	2.650
6.50-10		12	5.00F-10	590	182	18	212	9,00	TT	125	A5	2.145	1.650
23x10-12	250/60-12	20	8.00G-12	600	245	22	293	10,00	TT	145	A5	3.770	2.900
7.00-12		14	5.00S-12	680	191	18	230	9,00	TT	134	A5	2.755	2.120
7.00-12		16	5.00S-12	680	191	18	230	10,00	TT	136	A5	2.910	2.240
27x10-12	250/75-12	16	8.00G-12	685	250	22	293	8,00	TT	146	A5	3.900	3.000
27x10-12	250/75-12	24	8.00G-12	685	250	22	293	10,40	TT	155	A5	5.040	3.875
28x9-15	225/75-15 (8.15-15)	14	7.0-15	710	230	18	248	10,00	TT	146	A5	3.900	3.000
250-15	250/70-15	20	7.0-15	742	240	19	282	10,00	TT	155	A5	5.040	3.875
7.00-15	29x8-15	14	5.5-15	760	204	20	236	8,80	TT	140	A5	3.275	2.520
7.50-15		16	6.0-15	778	215	21	254	10,00	TT	146	A5	3.900	3.000
7.50-16	250/80-16	12	6.00G-16	805	220	21	254	8,00	TT	144	A5	3.630	2.790
300-15	315/70-15	20	8.0-15	840	290	23	345	9,00	TT	164	A5	6.500	5.000
8.25-15		14	6.5-15	841	247	19	281	8,00	TT	149	A5	4.225	3.250
8.25-15		16	6.5-15	841	247	19	281	9,30	TT	152	A5	4.615	3.550
355/65-15	32x12½-15 (350-15)	24	9.75-15	843	334	29	407	10,00	TT	170	A5	7.800	6.000
355/65-15	32x12½-15 (350-15)	32*	9.75-15	843	334	29	407	12,50	TT	177	A5	9.490	7.300
355/65-15	32x12½-15 (350-15)	32*	9.00-15	843	334	29	407	12,50	TL	177	A5	9.490	7.300
9.00-20	270/95-20	14	7.0-20	1.015	265	27	311	9,00	TT	160	A5	5.850	4.500
10.00-20	290/95-20	16	7.5-20	1.085	294	32	334	9,00	TT	164	A5	6.500	5.000
11.00-20	300/95-20	18	8.0-20	1.110	302	33	352	10,00	TT	170	A5	7.800	6.000
12.00-20	330/95-20	20	8.0-20	1.145	325	35	372	10,00	TT	176	A5	9.230	7.100
12.00-20	330/95-20	24	8.0-20	1.145	325	35	372	10,40	TT	178	A5	9.710	7.470
12.00-20	330/95-20	28	8.0-20	1.145	325	35	372	10,90	TT	180	A5	10.400	8.000
12.00-24	330/95-24	20	8.5-24	1.245	320	35	378	10,00	TT	178	A5	9.750	7.500
12.00-24	330/95-24	24	8.5-24	1.245	320	35	378	10,40	TT	178	A5	9.945	7.650
14.00-24	385/95-24	24	10.00W-24	1.360	380	39	450	10,00	TT/TL	186	A5	12.350	9.500
14.00-24	385/95-24	28*	10.00W-24	1.360	380	39	450	10,40	TT/TL	186	A5	12.600	9.690

* Requires special rim & components, please check with your local Trelleborg representative



Follow us

Yokohama TWS S.p.A.
Via Nazionale Tiburtina, 143 - 00019 Villa Adriana - Tivoli (RM), Italy
Phone: +39 0774 3841 – info.tws@yokohama-tws.com
www.trelleborg-tires.com



Shop our tires online



Discover our website