



Trelleborg

CX940

High resistance for medium intensity applications



The CX940 tire has been specially designed for container handling equipment such as reach stackers and top picks. This new tire with its robust casing and optimized tread design, ensures good stability, traction and load distribution. In addition, the cut and wear resistant compound minimizes risks of cuts and punctures, maximizing tire life.



**GOOD
STABILITY**



**EXTENDED
TIRE LIFE**



**WEAR RESISTANT
COMPOUND**



**REDUCED
TOTAL COST OF
OWNERSHIP**

1 Reinforced beads

Improved bead construction reduces stress on the bead when turning on-the-spot operations.



2 Wear resistant compound

High performing wear resistant compound minimizes tear and wear. The tire lasts longer, reducing heat generation and your machine downtime, lowering the cost per hour.




3 Wide tread contact area

The wide footprint area results in even wear, good stability and reduced vibration for operator comfort.



4 Deep tread depth

The deep tread provides longer tire life and boosts the efficiency of your machine.



Size	LI/SS	PR	Tread Pattern	In service		SLR mm	Tread depth mm	Permitted Rims	Tire Load Capacity (kg) 10,00 bar	Speed km/h
				SW mm	OD mm					
18.00 - 25 TL	207 A5	40	CX940	531	1658	761	64	13.00/2.5	26250	Static
									17500	25

The information and technical data provided in this catalogue are indicative and may be subject to change without prior notice. For up-to-date data and official product specifications, please refer to the product technical sheet available through your sales representative.



Shop our tires online



**Discover our website
and your legal guarantee rights**

Follow us

