



SR940. Designed for life.



**GET THE MOST OUT OF YOUR TIRES.
DESIGNED FOR MAXIMUM TIRE LIFE AND BEST COST PER HOUR.**





INTENSITY
MAXIMUM

SR940 Designed for life.

- 1 Unique tread pattern:**
Extra wide contact area to maximize tire life and stability
- 2 Side circumferential rib:**
Great handling and traction performance in wet conditions
- 3 Reinforced sidewall:**
Excellent stability during loading and unloading operations
- 4 Extra-deep tread:**
Superior tire life and best cost per hour



* TPMS: tire pressure management system
visit trelleborg.com/wheels for more information

SR940

MAXIMUM INTENSITY

Tire size	480/95 R 25
Service description LI/SS	208 A5
Index of tire strength	***
Permitted rims	13.00/2.5-25 11.25/2.0-25
Overall diameter - new [inch]	61.6
Rolling circumference - [inch]	191.8
Tread depth [32nd]	64
Tread pattern	SR 940
Type (tubeless/tube type)	TL
Section width - new [inch]	18.5
Loaded static radius [inch]	26.9
EAN code	8059971597202

Speed [mph]	Tire pressure [psi]				
	Tire load capacity [lbs]				
	116	123	130	138	145
0 Static	36,383	38,257	40,021	41,895	43,659
0.6 Creep	36,383	38,257	40,021	41,895	43,659
3	36,383	38,257	40,021	41,895	43,659
6	36,383	38,257	40,021	41,895	43,659
9	36,383	38,257	40,021	41,895	43,659
12	36,383	38,257	40,021	41,895	43,659
15	33,075	34,729	36,383	38,036	39,690
18	31,862	33,406	35,060	36,603	38,257
22	30,650	32,083	33,626	35,170	36,713



Trelleborg Wheel Systems Americas, Inc.
107 Audubon Road, Suite 205, Wakefield MA, 01880
www.trelleborg.com/wheels/us

[facebook.com/TrelleborgMaterialhandling](https://www.facebook.com/TrelleborgMaterialhandling) [youtube.com/TrelleborgMaterialhandling](https://www.youtube.com/TrelleborgMaterialhandling)

