



Trelleborg

CX940

Maximum resistance for high intensity applications



The CX940 tire has been specially designed for container handling equipment such as reach stackers and top picks. This new tire with its robust casing and optimized tread design, ensures high stability, excellent traction and superior load distribution. In addition, the cut and wear resistant compound minimizes risks of cuts and punctures, maximizing tire life.



**HIGH
STABILITY**



**EXTENDED
TIRE LIFE**



**WEAR RESISTANT
COMPOUND**



**REDUCED TOTAL
COST OF
OWNERSHIP**

1 Reinforced beads

Improved bead construction reduces stress on the bead when turning on-the-spot operations.



2 Wear resistant compound

High performing wear resistant compound minimizes tear and wear. The tire lasts longer, reducing heat generation and your machine downtime, lowering the cost per hour.




3 Wide tread contact area

The wide footprint area results in even wear, excellent stability and reduced vibration for operator comfort.



4 Deep tread depth

The deep tread provides longer tire life and boosts the efficiency of your machine.



Size	LI/SS	PR	Tread Pattern	In service		SLR (inches)	Tread depth (32 nd)	Permitted Rims	Tire Load Capacity (lbs) 145 psi	Speed (mph)
				SW (inches)	OD (inches)					
18.00 - 25 TL	207 A5	40	CX940	21	65	29.9	80	13.00/2.5	57,871	Static
									38,581	16



Printed on recycled paper



Discover our website

Follow us



Yokohama TWS North America, Inc.
107 Audubon Road - Building 2 - Suite 205
Wakefield, MA 01880
800-948-8473
info.tws@yokohama-tws.com
www.trelleborg-tires.com/en-us